

Dimension List

NB Size	OD Size	SKU No.	Tolerance O.D. (Min.)	Tolerance O.D. (Max.)	Nominal Wall Thickness	Weight per Foot in LBS	Hard Drawn W.P (PSI) ↑ •	Hard Drawn B.P (PSI) *
1/4"NB	0.375"	TC-T-FH-K-04	0.374"	0.376"	0.035"	0.145	1595	-
3/8"NB	0.500"	TC-T-FH-K-06	0.499"	0.501"	0.049"	0.269	1745	-
1/2"NB	0.625"	TC-T-FH-K-08	0.624"	0.626"	0.049"	0.344	1375	9840
5/8"NB	0.750"	TC-T-FH-K-10	0.749"	0.751"	0.049"	0.418	1135	-
3/4"NB	0.875"	TC-T-FH-K-12	0.874"	0.876"	0.065"	0.641	1315	9300
1"NB	1.125"	TC-T-FH-K-16	1.1235"	1.1265"	0.065"	0.839	1010	7200
1 1/4"NB	1.375"	TC-T-FH-K-20	1.3735"	1.3765"	0.065"	1.04	820	5525
1 1/2"NB	1.625"	TC-T-FH-K-24	1.623"	1.627"	0.072"	1.36	765	5000
2"NB	2.125"	TC-T-FH-K-32	2.123"	2.127"	0.083"	2.06	665	3915
2 1/2"NB	2.625"	TC-T-FH-K-40	2.623"	2.627"	0.095"	2.92	520	3575
3"NB	3.125"	TC-T-FH-K-48	3.123"	3.127"	0.109"	4.00	605	3450
3 1/2"NB	3.625"	-	3.623"	3.627"	0.120"	5.12	570	-
4"NB	4.125"	TC-T-FH-K-64	4.123"	4.127"	0.134"	6.51	555	3415
5"NB	5.125"	-	5.123"	5.127"	0.160"	9.67	540	3585
6"NB	6.125"	-	6.123"	6.127"	0.192"	13.87	540	3425
8"NB	8.125"	-	8.121"	8.127"	0.271"	25.90	580	3635
10"NB	10.125"	-	10.119"	10.127"	0.338"	40.30	585	-
12"NB	12.125"	-	12.119"	12.127"	0.405"	57.80	585	-