

Dimension List

NB Size	OD Size	SKU No.	Tolerance O.D. (Min.)	Tolerance O.D. (Max.)	Nominal Wall Thickness	Weight per Foot in LBS	Hard Drawn W.P (PSI) ↑ •	Hard Drawn B.P (PSI) *
1/4"NB	0.375"	TC-T-FH-L-04	0.374"	0.376"	0.030"	0.126	1350	-
3/8"NB	0.500"	TC-T-FH-L-06	0.499"	0.501"	0.035"	0.198	1195	-
1/2"NB	0.625"	TC-T-FH-L-08	0.624"	0.626"	0.040"	0.285	1105	7765
5/8"NB	0.750"	TC-T-FH-L-10	0.749"	0.751"	0.042"	0.362	965	-
3/4"NB	0.875"	TC-T-FH-L-12	0.874"	0.876"	0.045"	0.455	875	5900
1"NB	1.125"	TC-T-FH-L-16	1.1235"	1.1265"	0.050"	0.655	770	5115
1 1/4"NB	1.375"	TC-T-FH-L-20	1.3735"	1.3765"	0.055"	0.884	680	4550
1 1/2"NB	1.625"	TC-T-FH-L-24	1.623"	1.627"	0.060"	1.14	630	4100
2"NB	2.125"	TC-T-FH-L-32	2.123"	2.127"	0.070"	1.75	555	3365
2 1/2"NB	2.625"	TC-T-FH-L-40	2.623"	2.627"	0.080"	2.48	520	3215
3"NB	3.125"	TC-T-FH-L-48	3.123"	3.127"	0.090"	3.33	490	2865
3 1/2"NB	3.625"	-	3.623"	3.627"	0.100"	4.29	470	-
4"NB	4.125"	TC-T-FH-L-64	4.123"	4.127"	0.110"	5.38	450	2865
5"NB	5.125"	-	5.123"	5.127"	0.125"	7.61	410	2985
6"NB	6.125"	-	6.123"	6.127"	0.140"	10.2	385	2690
8"NB	8.125"	-	8.121"	8.127"	0.200"	19.29	420	2650
10"NB	10.125"	-	10.119"	10.127"	0.250"	30.1	425	-
12"NB	12.125"	-	12.119"	12.127"	0.280"	40.4	395	-